

# Circulation Water Bath

Model VS-1901W  
VS-1902WF  
VS-1902WF2

## Main Feature

- Multiful Use (Low/High Temp.)
- One-piece Stainless Steel Made
- Digital PID Controller
- Touch-Key Control
- Auto-tuning
- Easy to Use
- Internal/External Circulation Pump
- Temp. Maintenance / Heat exchanger



Circulation Water Bath	VS-1901W	VS-1902WF	VS-1902WF2
Temp. Range	RT +5℃ to 150℃	-20℃ to 150℃	-50℃ to 150℃
Compressor	none	1/3 HP	1/2 HP
Dimension ( IN )	495 x 290 x 150	325 x 290 x 150	325 x 290 x 150
Working Access	350 x 290	175 x 290	175 x 290
Capacity	21.5 Liter	14 Liter	14 Liter
Power	220V, 7A, 60Hz	220V, 9.5A, 60Hz	220V, 10.5A, 60Hz

## Specification

Temp. Accuracy	+/-0.1℃ at 37℃
Temp. Controller	Digital P.I.D. controller
Circulation Pump	16 Liter/min.
Material ( IN )	Stainless steel
( OUT )	Steel plate with powder coating
Lid	Stainless Steel, SUS 304
Safety Device	High/Low Temp. Protector, Water Level Sensor
Power	220V, 7A, 60Hz / 220V, 9.5A, 60Hz / 220V, 10.5A, 60Hz